Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050

 $\textcolor{red}{\textbf{e}} \ \text{admin@gamaconsulting.com.au}$ 

**w** www.gamaconsulting.com.au



# STORMWATER MANAGEMENT REPORT

PROJECT: 240888

DATE: January 2025

**CLIENT:** Samaris

SITE: 290 Unley Road, Hyde Park, SA



Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050 e admin@gamaconsulting.com.au

w www.gamaconsulting.com.au



# **Contents**

# 1.0 Overview

- 1.1 Background
- 1.2 Scope of assessment

# 2.0 Stormwater management strategy

- 2.1 Site description
- 2.2 Design criteria
- 2.3 Stormwater strategy
- 2.4 Hydrology/hydraulics
- 2.5 Hydraulic assessment
- 2.6 Water surface treatment

#### 3.0 Conclusion

APPENDIX A: RATIONAL METHOD CALCULATIONS APPENDIX B: STORMWATER MANAGEMENT PLAN C01

#### **DOCUMENT REVISION(S):**

| Revision | Description         | Date Issued:       | Report by:        |  |
|----------|---------------------|--------------------|-------------------|--|
| A        | Issued for approval | 19th December 2024 | Tyrone Franchitto |  |
| В        | Issued for approval | 16th January 2025  | Tyrone Franchitto |  |

# **Proprietary Information Statement**

This document and the information contained within, is proprietary and confidential. No part of this document may be disclosed in any manner to a third party without the prior written consent of gama consulting pty ltd.

All rights reserved. No section of this document may be amended, reproduced, removed, electronically transmitted without the written permission of gama consulting pty ltd.

© gama consulting pty ltd, 2019

Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050 e admin@gamaconsulting.com.au w www.gamaconsulting.com.au



# 1.Overview

# 1.1 Background

Gama Consulting have been engaged by Samaris Construction to prepare a conceptual Stormwater Management Plan (SMP) for the proposed new structure in Hyde Park.

This report is intended to conceptually outline the stormwater management design and detail methodology.

The report is based on the current Australian stormwater management procedures and in accordance with the requirements of the Institution of Engineers, Australia publication, Australia Rainfall and Runoff, 2019, Queensland Urban Drainage manual and Australian Standard 3500.3-2018.

# 1.2 Scope of assessment

The preparation of the plan comprises of the scope of services listed below:

 Prepare a Stormwater Management Plan detailing the proposed method of collection and disposal of site generated stormwater runoff.

# 2. Stormwater management strategy

#### 2.1 Site description

The subject site situated at corner of Unley Road with Esmond Street is currently occupied by existing retailing shops and a paved carpark at the rear. Refer Figure 1 – Site Aerial View

The site will be upgraded with a new structure to cover the whole site. Carpark and commercial use on the ground floor with residential space to occupy the upper floors.

Suite 3, 83 Fullarton Road, Kent Town SA 5067

**p** 08 7123 4050

e admin@gamaconsulting.com.au

**w** www.gamaconsulting.com.au





Figure 1 – Site Aerial View

In accordance with council Flood mapping the site is not affected by major stormwater events. Refer Figure 2 – Flood mapping



Figure 2 – Flood mapping

Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050 e admin@gamaconsulting.com.au w www.gamaconsulting.com.au



# 2.2 Design Criteria

The stormwater management strategy has been prepared as follows with consideration of the requirements:

- Post Development 1:100 Year stormwater runoff limited to Pre-Development 1:5 Year stormwater runoff.
- Ensure that the proposed will not impact adversely on the surrounding environment and existing residences during and after construction.

# 2.3 Stormwater management strategy

Based on stormwater requirements, the following stormwater management plan is proposed:

- 70% of the proposed roof area will be detained by new rainwater detention tanks
  with a controlled discharge orifice. This will be collected with a series of scattered
  downpipes with flying downpipes used along the carpark ceiling.
- 2 Outlets have been shown to the street
  - Outlet 1: Stormwater runoff from carpark and controlled rainwater tank overflow
  - Outlet 2: Un-detained stormwater runoff from front third of proposed roof structure.

Refer Site drainage plan for details.

# 2.4 Hydrology/hydraulics

A modeling assessment was undertaken to determine the rainfall-runoff relationship at the present site. The model had been designed using the rational method.

The following parameters and assumptions were made in the development of the drainage model for the site:

- run-off coefficients for roof=1, paving=0.9, landscaping =0.3
- Pipe losses not considered
- Rainfall Storm event data obtained from Bureau of Meteorology

#### **Pre-development**

| Catchment ID | Area(m <sup>2</sup> ) | Run-off coefficient |
|--------------|-----------------------|---------------------|
|              |                       | (C)                 |
| Roof         | 375                   | 1.0                 |
| Paving       | 268                   | 0.9                 |
| Landscaping  | 30                    | 0.3                 |
| Total        | 673                   |                     |

Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050

e admin@gamaconsulting.com.au www.gamaconsulting.com.au



# Post-development

| Catchment ID | Area(m <sup>2</sup> ) | Run-off coefficient |
|--------------|-----------------------|---------------------|
|              |                       | (C)                 |
| Roof         | 673                   | 1.0                 |
| Paving       | -                     | 0.9                 |
| Landscaping  | -                     | 0.3                 |
| Total        | 673                   |                     |

A detailed pre (1:5) and post-development (1:100) analysis is attached refer **Appendix**. **A**.

# 2.5 Hydraulic assessment

The model analyses were undertaken for several different scenarios (minor and major events) and respective pre- and post-development scenarios:

The stormwater calculations model output for different scenarios are summarised on Table 1

Table 1 - Flow rates for various scenarios

| Scenarios | Pre-development (20% AEP)<br>Flow Rate (L/s) | Post-development (1% AEP)<br>Flow Rate (L/s) |  |  |  |
|-----------|----------------------------------------------|----------------------------------------------|--|--|--|
|           | 14.15                                        | 14.14                                        |  |  |  |

# 2.6 Water surface treatment

Water quality targets required by EPA are:

- 90% retention of Gross Pollutants
- 80% retention of Total Suspended Solids
- 60% retention of Total Phosphorus
- 45% retention of Total Nitrogen
- MUSIC modelling is required to support the water quality improvement performance.

The proposed surface water treatment includes 2 Atlan smack filter baskets connected to grated pit and 1.0m long Atlan hydro channel to grated drain.

The Music model adopted simulates the proposed stormwater quality train above, please refer to the screenshot below.

Figure 6- Music model output

Suite 3, 83 Fullarton Road, Kent Town SA 5067

p 08 7123 4050

e admin@gamaconsulting.com.au

w www.gamaconsulting.com.au






Figure 3. Music outcome

# 3.0 Conclusion

The proposed stormwater drainage plan intends to demonstrate that the run-off from the proposed development will have no detrimental impact on the existing drainage system.

The run-off which will leave the site due to the proposed stormwater arrangements will be limited to the pre-development flow rates required.

Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050 e admin@gamaconsulting.com.au w www.gamaconsulting.com.au



# **APPENDIX A:**

# **RATIONAL METHOD CALCULATIONS**



Suite 3, 83 Fullarton Road, Kent Town SA 5067

p (08) 7123 4050

e admin@gamaconsulting.com.au w www.gamaconsulting.com.au ABN: 83 607 495796 JOB NO: 240888 SHEET:

Council: Unley

DATE: 19-Dec-24 ENG: TF

1

# STORMWATER CALCULATION

Site address: 290 Unley Road, Hyde Park

Site area: 673 m²
Soil type: Clayey

#### 1. Pre-development

Design ARI : 5 years
Duration : 5 min
Intensity : 81.5 mm/hr

 Intensity :
 81.5 mm/hr
 coefficient
 Q

 Roof area :
 375 m²
 →
 1.0
 8.49 L/s

 Paving area :
 268 m²
 →
 0.9
 5.46 L/s

 Landscaping area :
 30 m²
 →
 0.3
 0.20 L/s

Existing Flow, Q: 14.15 L/s

# 2. Post-development

No. dwellings: 1
Design ARI: 100 years
Duration: 5 min
Intensity: 181.0 mm/hr

Total To Street Detained coefficient Roof area:  $673\ m^{2}$ 202 m<sup>2</sup> 471 m² 1.0 Per. Paving area : 0 m<sup>2</sup>  $0 \text{ m}^2$ 0.5  $0\ m^{\scriptscriptstyle 2}$ Imper. Paving area:  $0 \text{ m}^2$ 0 m<sup>2</sup> 0 m<sup>2</sup> 0.9  $0 \text{ m}^2$  $0 \text{ m}^2$ 0 m<sup>2</sup> 0.3 Landscaping area:

 $\begin{tabular}{ll} Flow to Street, Q1: & 1 0.14 L/s \\ Flow from tank, Q2: & 4.00 L/s \\ Flow from detention, Q3: & 0.00 L/s \\ \end{tabular}$ 

#### 3. Detention

Detention system : RWT + Surface Detention

Critical storm duration, tc : 10 min

|                          |                      | RWT           |                | Surface Detention  |               |                |                    |                     |
|--------------------------|----------------------|---------------|----------------|--------------------|---------------|----------------|--------------------|---------------------|
| Duration (min)           | Intensity<br>(mm/hr) | Volume In (L) | Volume out (L) | Req. Volume<br>(L) | Volume In (L) | Volume out (L) | Req. Volume<br>(L) | Total Volume<br>(L) |
| 1                        | 278.0                | 2181          | 2642.31        | -461               | 0             | 0              | 0                  | -461                |
| 3                        | 220.0                | 5178          | 3122.73        | 2056               | 0             | 0              | 0                  | 2056                |
| 5                        | 181.0                | 7100          | 3603.15        | 3497               | 0             | 0              | 0                  | 3497                |
| 10                       | 131.0                | 10278         | 4804.2         | 5474               | 0             | 0              | 0                  | 5474                |
| 15                       | 105.0                | 12357         | 6005.25        | 6352               | 0             | 0              | 0                  | 6352                |
| 20                       | 89.3                 | 14013         | 7206.3         | 6806               | 0             | 0              | 0                  | 6806                |
| 25                       | 78.4                 | 15378         | 8407.35        | 6970               | 0             | 0              | 0                  | 6970                |
| 30                       | 70.3                 | 16547         | 9608.4         | 6938               | 0             | 0              | 0                  | 6938                |
| 45                       | 54.7                 | 19313         | 13211.55       | 6101               | 0             | 0              | 0                  | 6101                |
| 60                       | 45.6                 | 21466         | 16814.7        | 4651               | 0             | 0              | 0                  | 4651                |
| 90                       | 34.9                 | 24644         | 24021          | 623                | 0             | 0              | 0                  | 623                 |
| 120                      | 28.8                 | 27115         | 31227.3        | -4112              | 0             | 0              | 0                  | -4112               |
| 180                      | 21.7                 | 30646         | 45639.9        | -14994             | 0             | 0              | 0                  | -14994              |
| 270                      | 16.3                 | 34530         | 67258.8        | -32729             | 0             | 0              | 0                  | -32729              |
| 360                      | 13.2                 | 37283         | 88877.7        | -51594             | 0             | 0              | 0                  | -51594              |
| Minimum Detention Volume |                      |               | 6,970 Ltr      | (per dwelling)     |               | Ltr            |                    |                     |



gama consulting Suite 3, 83 Fullarton Road, Kent Town SA 5067 p (08) 7123 4050

e admin@gamaconsulting.com.au w www.gamaconsulting.com.au ABN: 83 607 495796

**JOB NO**: 240888 SHEET: 2

**DATE**: 19-Dec-24 ENG: TF

# 4. Orifice size

<u>RWT</u>

Height, H: 1 m Velocity, V: 4.4 m/s Flow out, Q: 4.00 L/s

A : 0.00148 m<sup>2</sup>


Max. Orifice Diameter : 43 mm

Suite 3, 83 Fullarton Road, Kent Town SA 5067 p 08 7123 4050 e admin@gamaconsulting.com.au w www.gamaconsulting.com.au



# **APPENDIX B:**

# **STORMWATER MANAGEMENT PLAN C01**



SCALE 1:100

admin@gamaconsulting.com.a www.gamaconsulting.com.au

THIS DRAWING IS COPYRIGHT (C) AND REMAINS THE PROPERTY OF GAMA CONSULTING PTY

SAMARAS CONSTRUCTION & DEVELOPMENTS

**SCALE 1:200** 

ISSUED FOR REVIEW

REVISION DESCRIPTION

09/12/24

DATE CHK

THIS IS AN ENGINEERING SURVEY PLAN, AND SHOULD NOT BE TAKEN AS A CADASTRAL OR IDENTIFICATION SURVEY. BOUNDARY DATA SHOWN IS TO BE

ALL SITE LEVELS AND DETAILS MUST BE CHECKED AND APPROVED BY THE

COVER TO PIPES SHALL COMPLY WITH AS 3500.5. PIPES LESS THAN 200mm BELOW THE FINISHED SURFACE UNDER THE DRIVEWAYS SHALL BE ENCASED IN

ANY DISCREPANCIES TO BE REFERRED TO THIS OFFICE FOR CLARIFICATION


7000L MIN. CAPACITY RAINWATER DETENTION TANK/S

DRAWING No. **240888** 

C01

COUNCIL

UNLEY



# FW: 240888: 24037925: Unit 1-3 290 Unley Rd Hyde Park - Updated Stormwater Management Report

From Corey Polyak <cpolyak@urps.com.au>

Date Thu 16/01/2025 4:33 PM

To Khan, Adnan (DHUD) <Adnan.Khan@sa.gov.au>; Amelia DeRuvo <Aderuvo@unley.sa.gov.au>

1 attachment (2 MB)

2025.01.16.240888.StormwaterReport - B.pdf;

# **OFFICIAL**

Hi Adnan and Amelia,

Please see attached updated Stormwater report and comments below.

Kind Regards,



# **Corey Polyak**

Consultant High Rise & Commercial Development 0423 253 645

27 Halifax Street Enter via Symonds Pl Adelaide SA 5000 08 8333 7999

Our office will be closed from 12pm 20 Dec 2024 and reopening 6 Jan 2025.

## **Kaurna Country**

The contents of this email are confidential. No representation is made that this email is free of viruses or other defects. Virus scanning is recommended and is the responsibility of the recipient.

If you have received this communication in error, you must not copy or distribute this message or any part of it or otherwise disclose its contents to anyone.

From: Hamish Bills <hamishb@gamaconsulting.com.au>

**Sent:** Thursday, January 16, 2025 3:00 PM **To:** Corey Polyak <cpolyak@urps.com.au>

**Cc:** Tyrone Franchitto <tyronef@gamaconsulting.com.au>; Russell Biar <rbiar@samarasgroup.com>; Matthew King <mking@urps.com.au>; Matthew Mammone <mattm@gamaconsulting.com.au>; Scott Meek

<scott@sm-f.com.au>; lan.Bishop@salt3.com.au; Sarah Swincer <sarah@sm-f.com.au>

Subject: 240888: 24037925: Unit 1-3 290 Unley Rd Hyde Park - Updated Stormwater Management Report

You don't often get email from <a href="mailto:hamishb@gamaconsulting.com.au">hamishb@gamaconsulting.com.au</a>. <a href="mailto:hearn why this is important">Learn why this is important</a>

Afternoon Corey,

Please find our updated Stormwater Management Report (RevB).

We have also responded to council questions in red below.

i.e.

In addition to Council's formal Reg 23 referral response, we provide the following commentary regarding the prescribed matters:

Section 2.4 – existing impervious runoff coefficient should be corrected. Only a small area has been applied at 0.3.

# Run-off coefficients noted correctly in the amended report

- No pollutant filter has been nominated for surface water collected via the GIP per the planning report. Oil and sediment removal to be demonstrated. Refer to MUSIC output in report.
- To what degree does this strategy minimise the discharge of sediment, suspended solids, organic
  matter, nutrients, bacteria, litter and other contaminants to the stormwater system. Will EPA Water
  quality targets be achieved.

Refer water quality treatment proposed achieved the EPA targets, refer amended report

Planning report notes the rainwater tank will be underground, however I understand the SMP was
outstanding at the time. Please confirm, the tanks will be above ground and flow via gravity to the kerb
outlet (overflow outlet as well as 43mm orifice outlet).

Rainwater tank is above the ground and overflow gravity drain to kerb

With respect to FFL's, surrounding footpath levels are to be max 2.5% in order to meet DDA compliance.
 Note added to site plan drawing

Regards Hamish Bills– Director



Suite 3/83 Fullarton Road, Kent Town, 5067

p: 08 7123 4050 mob: 0402 407 885

e: <a href="mailto:hamishb@gamaconsulting.com.au">hamishb@gamaconsulting.com.au</a> w: <a href="mailto:www.gamaconsulting.com.au">www.gamaconsulting.com.au</a>

A Please consider the environment before printing this email – Thank you

This message may contain privileged and confidential information. It may be read, copied and used only by the addressee. If you have received it in error, please contact us (Gama Consulting Pty Ltd) immediately and delete the message from your system including any copies. This message and any attachments may only be used if the recipient accepts responsibility for the accuracy of data transmitted by electronic means. If the recipient does not accept this responsibility the information contained herein shall not be used. Copyright of the documents remains with Gama Consulting Pty Ltd. Although we have used reasonable efforts to ensure that this message and any attachments are free from viruses, it is the responsibility of the recipient to ensure that they are virus free. Gama Consulting Pty Ltd.. excludes liability, to the fullest extent permitted by law for any direct, indirect or consequential loss, damage, costs or expenses in any way caused by a virus in this message or any attachments.